

Polaris Material Safety Data Sheet

Polaris Sales Inc.
2100 Highway 55
Medina, MN 55340

Emergency: 800-424-9300
Information: 763-542-0500

SECTION 1 CHEMICAL PRODUCT IDENTIFICATION

Product: Polaris Premium Starter Grease
Synonyms/Other: Not Applicable
Item Number(s): 2871460
MSDS Number: 0410
Product Type: Specialty grease
Preparation/Revision Date: 07/30/2007

SECTION 2 COMPOSITION INFORMATION

INGREDIENTS	CAS #	%	OSHA TWA (PEL)	OSHA STEL	ACGIH TWA	SKIN
Solvent-refined Light Paraffinic Petroleum Distillate*	064741895	48	5 mg/m ³ (PEL)	10 mg/m ³	5 mg/m ³ (TLV)	NO
Molybdenum disulfide	001317335	16	10 mg/m ³ (PEL)	--	10 mg/m ³ (TWA)	NO
Zinc pyrophosphate	007446266	13	Not established	Not established	Not established	--
Silica, amorphous	007631869	2	15 mg/m ³ (PEL)total dust 5mg/m3 respirable fraction	--	10 mg/m ³ (TLV) inhalable particulate 3 mg/m ³ respirable particulate	--
Aluminum phosphate	007784307	2	For soluble salts of Aluminum 2 mg/m ³ (PEL)	--	For soluble salts of Aluminum 2 mg/m ³ (TLV)	--
Hydrotreated neutral oil, C ₁₅ -C ₃₀	072623860	2	Not established	Not established	Not established	NO
Ethylene distearylamine	000110305	3	Not established	Not established	Not established	--

Comments: The above components are hazardous as defined in 29 CFR 1910.1200.
 * - Applicable to oil mist, not defined for base oils.
 TWA – Time Weighted Average is the employee’s average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be exceeded.
 STEL – Short Term Exposure Limit is the employee’s 15-minute time weighted average exposure which shall not be exceeded at any time during a work day unless another time limit is specified.

SECTION 3 HAZARDOUS IDENTIFICATION

WARNING: - MAY CAUSE EYE IRRITATION
 - MAY CAUSE SKIN IRRITATION

Eye contact: Direct contact may cause irritation, redness, tearing and blurred vision.

Skin contact: Avoid prolonged skin contact. This product contains materials that may cause skin irritation. Prolonged or repeated contact may result in dermatitis (dryness, chapping and reddening of skin.)

Polaris Material Safety Data Sheet

Inhalation:	Short vapor exposure may cause drowsiness, irritate nose and throat and cause injury to the following organ (s) : Nervous system.
Ingestion:	Do not ingest. Product is expected to be relatively non-toxic unless lung aspiration occurs. Aspiration is not expected with this material due to thickness or product. Coughing, choking and gagging are often noted at the time of aspiration should it occur. This product has laxative properties and may result in abdominal cramps and diarrhea.
Other:	Not applicable.

SECTION 4 FIRST AID MEASURES

Eye contact:	Check for and remove contact lenses. Flush eyes with cool, clean, low-pressure water for at least 15 minutes. Hold eyelids apart to ensure complete irrigation of the eye and eyelid tissue. If irritation persists seek medical attention. If material is hot, treat for thermal burns and take victim to hospital immediately.
Skin contact:	Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs, seek medical attention. If material is hot, submerge injured area in cold water. If victim is severely burned, remove to a hospital immediately. Wash contaminated clothing before reuse. Of special caution is sub-cutaneous grease injection due to high pressure. Victim may not be aware of injected material. Contact a physician as soon as possible for removal of the injected grease.
Inhalation:	If overcome by inhalation of hot vapors, remove to fresh air. Use oxygen if there is difficulty breathing or artificial respiration if breathing has stopped. Do not leave victim unattended. Seek immediate medical attention if necessary.
Ingestion:	Do not induce vomiting. If spontaneous vomiting occurs keep head below hips to prevent aspiration and monitor for breathing difficulty. Gastric lavage should be performed only by qualified medical personnel. Keep affected person warm and at rest. Seek immediate medical attention.
Other:	Not applicable.

SECTION 5 FIRE FIGHTING MEASURES

Flash point:	100°C (212°F) by ASTM D 92.
Flammable limits:	Not determined.
Extinguishing media:	Not determined.
Special firefighting procedures:	Evacuate area and fight fire from a safe distance. If leak or spill has not ignited, ventilate area and use water spray to disperse gas or vapor and to protect personnel attempting to stop a leak. Use water spray to cool adjacent structures and to protect personnel. Shut off source of flow if possible (safely). Stay away from storage tank ends. Withdraw immediately in case of rising sound from venting safety device or any discoloration of storage tank due to fire. Fire fighters must wear MSHA/NIOSH approved positive pressure breathing apparatus (SCBA) with full face mask and full protective equipment.
Unusual fire & explosion hazards:	Dense smoke may be generated while burning. Toxic fumes, gases or vapors may evolve on burning. High temperatures may create heavy flammable vapors that may settle along ground level and low spots to create an invisible fire hazard.
Byproducts of combustion:	Fires involving this product may release oxides of carbon, Phosphorous, nitrogen and sulfur; reactive hydrocarbons and irritating vapors.
Autoignition temperature:	Not determined.
Explosion data:	Not determined.
Other:	Not applicable.

Polaris Material Safety Data Sheet

SECTION 6

ACCIDENTAL RELEASE MEASURES

Spill control procedures (land):

Immediately turn off or isolate any source of ignition (pilot lights, electrical equipment, flames, heaters, etc.). Evacuate area and ventilate. Personnel wearing proper protective equipment should contain spill immediately with inert materials (sand, earth, chemical spill pads of cotton) by forming dikes. Dikes should be placed to contain spill in a manner that will prevent material from entering sewers and waterways. Large spill, once contained, may be picked up using explosion proof, non-sparking vacuum pumps, shovels, or buckets, and disposed of in suitable containers for disposal. If a large spill occurs notify appropriate authorities. In case of road spill or accident contact Chem-Trec (800-424-9300).

Spill control procedures (water):

This product is a semi-solid with low water solubility. Material will form clumps on water surfaces and spread by wave motion. Try to contain large spills with floating booms to prevent spill from spreading. Remove from surface by skimming or with suitable adsorbents. If a large spill occurs notify appropriate authorities (normally the National Response Center or Coast Guard at 800-424-8802).

Waste disposal method:

Most oil based products are incinerated, land-filled or reclaimed. All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. See Section 14.

Other:

CAUTION - If spilled material is cleaned up using a regulated solvent, the resulting waste mixture will be regulated.

SECTION 7

HANDLING AND STORAGE

Handling procedures:

Keep containers closed when not in use. Do not transfer to unmarked containers. Fire extinguishers should be kept readily available. See NFPA 30 and OSHA 1910.106 -- Flammable and Combustible Liquids. Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld, or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

Storage procedures:

Handling temperatures should not exceed 60°C (140°F) to minimize danger of burns. Open containers carefully in a well ventilated area or use appropriate respiratory protection. Wash thoroughly after handling.

Store containers away from heat, sparks, open flame, or oxidizing materials. Product should not be stored above 45°C (113°F). Extended storage at excessive temperatures may produce odorous and toxic fumes from product decomposition.

Additional information:

No additional information.

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection:

Applicable mainly to persons in repeated contact situations such as packaging of product, service/maintenance, and cleanup/spill control personnel.

Respiratory protection:

None required if airborne concentrations are maintained below threshold limits listed on page one. Otherwise a respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed. Where misting may occur, wear an MSHA/NIOSH approved (or equivalent) half-mask form dust/mist air purifying respirator.

Eye protection:

Eye protection is strongly recommended. If material is handled such that it could be splashed into the eyes, wear safety glasses with side shields or vented/splash proof goggles (ANSI Z87.1 or approved equivalent).

Hand protection:

Impervious gloves such as neoprene or nitrile rubber to avoid skin sensitization and absorption.

Polaris Material Safety Data Sheet

Other protection: Use of an apron and overboots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization and absorption. If handling hot material use insulated protective equipment. Launder soiled clothes. Properly dispose of contaminated leather articles and other materials which cannot be decontaminated.

Local control measures: Use adequate ventilation when working with material in an enclosed area. Mechanical methods such as fume hoods or area fans may be used to reduce localized vapor/mist areas. If vapor or mist is generated when the material handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure. Eyewash stations and showers should be available in areas where this material is used and stored.

Other: Consumption of food and drink should be avoided in work areas where product is present. Always wash hands and face with soap and water before eating, drinking or smoking.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Vapor pressure: Not applicable.
API gravity: Not determined.
Density: Not determined.
Specific gravity: 1.35 @ 25°C
Solubility: Negligible in water, miscible in most petroleum solvents.
Percent volatile: Not determined.
Vapor density (air=1): >1.
Evaporation rate (n-Butyl Acetate=1): Not applicable
Odor: Slight odor
Appearance: Charcoal gray
Viscosity: Not applicable.
Boiling point: Not applicable.
Pour/Freeze point: Not applicable.
Other: Not applicable.

SECTION 10 STABILITY AND REACTIVITY

Stability: Material is stable at room temperatures and pressure.
Conditions to avoid: Avoid high temperatures and product contamination.
Incompatibility with other materials: Avoid contact with acids and oxidizing materials.
Decomposition products: Smoke, carbon monoxide and dioxide, and other aldehydes of incomplete combustion. Oxides of carbon, nitrogen and sulfur; reactive hydrocarbons and irritating vapors.
Hazardous polymerization: Will not occur.
Other: Not applicable.

SECTION 11 TOXICOLOGICAL INFORMATION

Oral toxicity: Not determined.
Dermal toxicity: Not determined.
Inhalation toxicity: Negligible risk due to very low vapor pressure (physical form is a solid).
Dermal sensitization: Prolonged or repeated contact may make skin more sensitive to other skin sensitizers. Based on data from similar materials.
Chronic toxicity: Not determined.
Carcinogenicity: The components of this material are not listed by IARC, NTP, OSHA or ACGIH as known or suspected carcinogens.
Mutagenicity: Not determined.
Reproductive toxicity: Not determined.
Other: This product contains petroleum base oils which may be refined by various

Polaris Material Safety Data Sheet

processes including severe solvent extraction, severe hydrocracking, or severe hydrotreating. None of the oils require a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as; carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B).

SECTION 12 ECOLOGICAL INFORMATION

Environmental toxicity: This material may be toxic to aquatic organisms and should be kept out of sewage and drainage systems and all bodies of water.
Environmental fate: Not determined.
Other: Not applicable.

SECTION 13 DISPOSAL CONSIDERATIONS

Waste disposal: Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. This product unadulterated by other materials may be classified as a non-regulated waste in some areas - but still needs to be disposed of at approved facilities. Waste management should be in full compliance with federal, state, and local laws.
Disposal consideration: Most used and non-use oils and greases are incinerated by licensed burner facilities for heat value, or reclaimed by oil recycling services. Look in a local telephone directory or internet for headings under, 'Waste', 'Waste Services', 'Waste Disposal' for companies licensed to handle such material. Additional information can be obtained from local EPA, DNR, Sewer and Land-Fill sites. Unused, packaged fluids may be donated to other companies or charities (fluids MUST be unused).
Other: The transportation, storage, treatment and disposal of RCRA waste material must be conducted in compliance with 40 CFR 262, 263, 264, 268 and 270. Disposal can only occur in properly permitted facilities. Check state and local regulations for any additional requirements as these may be more restrictive than federal laws and regulations. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this MSDS incomplete, inaccurate or otherwise inappropriate. Disposal of this material must be conducted in compliance with all federal, state, and local regulations.

SECTION 14 TRANSPORT INFORMATION

U.S. DOT shipping description: Not regulated.
U.S. DOT identification number: Not regulated.
U.S. DOT hazard classification: Not applicable.
Packaging class: Not applicable.
Other: Not applicable.

SECTION 15 REGULATORY INFORMATION

Clean water act/oil pollution act: Under Section 311 of the Clean Water Act (40 CFR 110) and the Oil Pollution Control Act of 1990, this material is considered an oil. Any spill or discharges that produce a visible sheen or film on surface of water, or in waterways, ditches, or sewers leading to surface water must be reported. Contact the National Response Center at 800-424-8802.
TSCA: All components of this material are listed in the U.S. TSCA Inventory.
Other TSCA: Not applicable.
SARA Title III: Section 302/304 extremely hazardous substances:

Polaris Material Safety Data Sheet

None.

Section 311, 312 hazard categorization:

Acute (immediate health effects):	Yes
Chronic (delayed health effects):	Yes
Fire (hazard):	NO
Reactivity (hazard):	NO
Pressure (sudden release hazard):	NO

Section 313 toxic chemicals:

Zinc compounds (CAS 68649-42-3).

CERCLA:

For stationary/moving sources – reportable quantity (due to):
Not applicable.

Other:

A release of this product, as supplied, is exempt from reporting under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) by the petroleum exclusion. However, releases may be reportable to the Nation Response Center under the Clean Water Act, 33 U.S.C. 1321(b)(3) and (5) - see head of Section 15. Failure to report may result in substantial civil and criminal penalties.

Recommend contacting the local authorities in the event of any type of spill to determine local reporting requirements and also to aid in the cleanup.

SECTION 16	OTHER INFORMATION
-------------------	--------------------------

	NFPA 704	NPCA-HMIS	KEY
HEALTH:	2	--	0 = Minimal
FIRE:	1	--	1 = Slight
REACTIVITY:	0	--	2 = Moderate
SPECIFIC HAZARD:	NONE	--	3 = Serious
PROTECTION INDEX:	N/A	--	4 = Severe

Precautionary labels: - MAY CAUSE EYE IRRITATION
 - MAY CAUSE SKIN IRRITATION

External information: This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used. Polaris must rely on information provided by those materials manufacturers or distributors.

Creation date: 06/03/2000
File: Polaris Premium Starter Grease (0410)
Version: II

INFORMATION PROVIDED IN THIS MSDS IS CONSIDERED ACCURATE AND RELIABLE BASED ON INFORMATION ISSUED FROM INTERNAL AND OUTSIDE SOURCES TO THE BEST OF POLARIS'S KNOWLEDGE. HOWEVER, POLARIS MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, OF MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, REGARDING THE ACCURACY OF SUCH INFORMATION OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF, OR AS TO THE SUFFICIENCY OF THE INFORMATION HEREIN PRESENTED. POLARIS ASSUMES NO RESPONSIBILITY FOR INJURY TO RECIPIENT OR TO THIRD PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND RECIPIENT ASSUMES ALL SUCH RISKS.

Revisions / Comments:

Updated and revised the following:
MSDS format verion G
MSDS header (telephone area code change)
Section 1
Section 2
Section 14
Section 15
Section 16
MSDS reviewed: 07/30/2007